

jetNEXUS Enterprise Range Specifications



jetNEXUS Application Firewall Available as an Extra Option

* Tests were network bound.

	ETM-E4	ETM-E5
Chassis	1U Half depth	1U Full depth
CPU	Quad core	2 x Hex core
Memory	8GB	12GB - 64GB
Network Interface	4 x 10/100/1000	8 x 10/100/1000
Max Interface	8 x 10/100/1000	16 x 10/100/1000 or 2 x 10GbE
Layer 4 - Connections Per Second	67K	112K
Layer 7 – HTTP Connections Per Second	96K	157K
Layer 7 – HTTP Requests Per Second (0k)	212K	490K
Layer 7 – HTTP Requests Per Second (2k)	154K	312K
Layer 7 – HTTP Requests Per Second (8k)	117K	261K
HTTP Max Throughput	8 Gbps	25 Gbps*
SSL Transaction Per Second (1024 bit RSA, RC4, no session reuse)	10K	25K
SSL Max Throughput	3.6 Gbps	9.8 Gbps
HTTP Cache Requests Per Second	402K	936K
HTTP Cache Max Throughput	10 Gbps	30 Gbps*

jetNEXUS

Tel: +44 (0) 870 382 5050

Fax: +44 (0) 870 382 5520

Email: info@jetnexus.com

Web: www.jetnexus.com

jetNEXUS provide innovative, market leading solutions for application acceleration, load balancing and application delivery technology.

jetNEXUS solutions improve the performance, scalability, reliability and manageability of applications. Our product portfolio is accessible to a wide and varied client base, ranging from simple, cost effectively focused solutions to Enterprise-grade application delivery controllers.